DD 3050 Weld-in thermowell according to DIN43772 Form 4

Thermowell

Design	Drilled bar stock (solid machined)
Process connection	Weld-in

Material

Stock items	Wst. 1.4571, 1.4404, 1.7335, 1.5415, 1.0460
Other materials	To specify

Stem / Shrank

Wetted part	Tapered

Dimensions

Length L1, L2, L3.	See table
Standard	According DIN 43772 Form 4
Bore Size	7mm
Tolerance	H7

Options

Other dimensions or bore size
Plug and chain for test wells
Tagging
Wake frequency calculation



Type	L1	L2	L3	D1	D2	Connect.
D1	140	50	65	24	12,5	M18x1.5
D2	200	50	125	24	12,5	M18x1.5
D3	200	50	125	30	16	M18x1.5
D4	200	110	65	24	12,5	M18x1.5
D5	260	110	125	24	12.5	M18x1.5
D6	225	105	125	30	16	M18x1.5

Ordering code

Model	DD 3050		
Material			↑
Type		↑	

thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo-electra.com
http://www.thermo-electra.com