



PE 142/12

EU DECLARATION OF CONFORMITY

Manufacturer: Pyropress Limited
Address: Bell Close, Plympton, Plymouth, Devon, England, PL7 4JH

The Manufacturer hereby declares that the Flameproof products: -

Titan Type: PF261 PR261, PF262, PR261 Pressure Switch
PF263, PR263, PF264, PR264 High Pressure Switch.
DPF265, DPR265, DPF266, DPR266 Differential Pressure Switch.
PF266, PR266 Low Pressure Switch.
VF266, VR266 Vacuum Switch.
DPF296, DPR296, High Static Differential Pressure Switch
TF171, TR171, TE171, TF172, TR172, TE172, Temperature Switch.
TF175, TR175, TF176, TR176 Capillary Temperature Switch.
FF503, FR503 Flow Switch.
LF34, LR34 Horizontal Level Switch.
LF35, LR35 Vertical Switch.

Comply with the requirements of:

EU Directive 2014/34/EU, for the use in potentially explosive atmospheres:
II 2 G Ex db IIB+H₂ T6...T2 Gb. Certified: Tamb -60°C to +40°C.... +90°C

International Electrotechnical Commission IEC Certification Scheme for Explosion Atmospheres
Ex db IIB+H₂ T6...T2 Gb. Certified: Tamb -60°C to +40°C.... +90°C

When used within the limitations and conditions of the product specifications & working instructions.

EC Type Examination Certificate Number: ExVeritas 19ATEX0501X

IECEX Type Examination Certificate Number: IECEX EXV 19.0031X

Harmonised standards applied: EN 60079-0: 2018, EN60079-1: 2014

Standards applied: IEC 60079-0: 2017 and IEC 60079-1: 2014-06

Other Directives applied: Pressure Equipment 2014/68/EU, Sound Engineering Practice (SEP),
Chapter 1, Article 4 (3).

Other Standards applied: Ingress Protection, BS EN 60529:1992+A2:2013,
IEC 60529:1989+A1:1999+A2:2013; IP66 rated.

Notified Body responsible for Quality Assurance:

Intertek Italia Spa, Via Guido Miglioli, 2/A, 20063 Cernusco sul Naviglio (MI), Italy.
Notified body No 2575.

Notified Body responsible for EU Type Examination Certificate:

ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark.
Notified body No 2804

Notified Body responsible for IECEX Type Examination Certificates:

ExVeritas, Units 16-18, Abenbury Way, Wrexham Industrial Estate, Wrexham, LL13 9UZ, UK.
Notified body No 2585.

Equipment Specification: Product specifications are listed in the Technical file TCF 1002

This Declaration may only be used in its entirety & without change.

Modification of this equipment / product without prior approval from Pyropress Limited will render this declaration null & void.

Stephen Burns, Managing Director, on behalf of Pyropress Limited

Signed..........Dated.....30th October 2020.

1 **EU - Type Examination Certificate**

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

3 Certificate Number: ExVeritas 19ATEX0501X Issue: 1

4 Equipment: Titan Ex db Switch

5 Manufacturer: Pyropress Ltd

6 Address: Bell Close,
Plympton,
Plymouth,
Devon PL7 4JH UK

7 This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

8 ExVeritas, Notified Body number 2804 in accordance with Article 17 of the Council Directive 2014/34/EU of 26 February 2014, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to design and construction of equipment and protective systems for use in potentially explosive atmospheres given in Annex II to the Directive


9 Compliance with the applicable Essential Health and Safety Requirements has been assured by compliance with the following Standards and section 16 of this certificate:

EN 60079-0: 2018 EN 60079-1: 2014

10 If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

11 This EU-Type Examination Certificate relates only to the design, construction, examination and tests of the specified equipment or protective system in accordance to the Directive 2014/34/EU. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.

12 The marking of the equipment shall include the following:

 II 2 G Ex db IIB + H₂ T6.....T2 Gb Tamb -60°C to +40°C+90°C



This certificate may only be reproduced in its entirety and without any change, schedule included.
The certificate is only valid when it carries an original signature.
For help or assistance relating to this certificate, contact info@exveritas.com.
ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark..
ExVeritas® is a registered trademark, unauthorised use will lead to prosecution.

Schedule

13 Description of Equipment or Protective System

The Titan switch is intended to sense changes in temperature, pressure, level or flow via the use of mechanical actuators. The generic two-chamber enclosure is utilised for all applications and is constructed from aluminium LM25TF or material of greater tensile strength. One chamber contains the means (where necessary) of adjusting the set-point(s) whilst the other houses either a single or dual microswitch assembly. The Titan switch possesses five flamepaths. The respective switch outer case-top cover and switch outer case-electrical entry interfaces are of the flange type. The guide-operating rod interface is of the cylindrical type. And the respective switch outer case-guide and electrical entry-adaptor interfaces are of the threaded type with the latter always utilising a suitably certified adaptor. The maximum internal free volume of the flameproof chamber is 99cc. The limits on the ambient and process temperatures and the internal power dissipation shown in the table below ensure that the equipment does not exceed the maximum surface temperature of any given T Class:

T Class	Ambient Temperature Range (°C)	Permitted Process Temperature (°C)	Power Rating (W)
T6	-60 to +75	-60 to +65	2.5
T6	-60 to +70	-60 to +65	5
T6	-60 to +60	-60 to +65	10
T6	-60 to +50	-60 to +65	15
T6	-60 to +40	-60 to +55	20
T5	-60 to +90	-60 to +80	2.5
T5	-60 to +75	-60 to +80	10
T5	-60 to +70	-60 to +75	12.5
T5	-60 to +60	-60 to +70	17.5
T5	-60 to +50	-60 to +65	22.5
T5	-60 to +40	-60 to +60	27.5
T4	-60 to +90	-60 to +130	2.5
T4	-60 to +75	-60 to +130	10
T4	-60 to +70	-60 to +130	12.5
T4	-60 to +60	-60 to +130	17.5
T4	-60 to +50	-60 to +130	22.5
T4	-60 to +40	-60 to +130	27.5
T3	-60 to +90	-60 to +195	2.5
T3	-60 to +75	-60 to +195	10
T3	-60 to +70	-60 to +195	12.5
T3	-60 to +60	-60 to +195	17.5
T3	-60 to +50	-60 to +195	22.5
T3	-60 to +40	-60 to +195	27.5
T2	-60 to +90	-60 to +280	2.5
T2	-60 to +75	-60 to +280	10
T2	-60 to +70	-60 to +280	12.5
T2	-60 to +60	-60 to +280	17.5
T2	-60 to +50	-60 to +280	22.5
T2	-60 to +40	-60 to +280	27.5

Certificate: ExVeritas 19 ATEX 0501X Issue 1

This certificate may only be reproduced in its entirety and without any change, schedule included.

For help or assistance relating to this certificate, contact info@exveritas.com.

ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark.

ExVeritas® is a registered trademark, unauthorised use will lead to prosecution.

Schedule

13.1 Detail of changes

Issue 1

- Transfer of certificate to Danish NB – no drawing changes

14 Descriptive Documents

14.1 Associated Report and Certificate History:

Report Number	Cert Issue Date	Issue	Comment
R2133/A/1	8 Jul 2019	0	Initial issue of the Prime Certificate
N/A – ExV3035	31 Oct 2020	1	Transfer of the certificate from ExVeritas UK, Notified Body number 2585 to ExVeritas Denmark, Notified Body number 2804. Certificate number remains unchanged.

14.2 Compliance Drawings:

Issue 0

Title:	Drawing No.:	Rev. Level:	Sheets	Date:
Certification Drawing Titan Ex db Switch	1340/A1	3	1 of 1	16.04.19
Certification Drawing Labels, Titan Ex db Switch	1341/A3	3	1 of 1	16.04.19

15 Conditions of Certification

15.1 Special Conditions for Safe Use

- Flameproof joints not intended for repair
- Suitably rated cable must be selected if the equipment is subject to service temperatures of 70°C or greater
- Fasteners associated with the flange flamepaths possess a minimum yield strength of 240 N/mm²

15.2 Conditions for Use – Manufacturer’s responsibility
None

16 Essential Health and Safety Requirements

Essential Health and Safety Requirements are addressed by the standards listed in section 9 and where required the report listed in section 14.1

The manufacturer shall inform the Notified Body of any modifications to the design of the product described by this schedule.

Certificate: ExVeritas 19 ATEX 0501X Issue 1

This certificate may only be reproduced in its entirety and without any change, schedule included.

For help or assistance relating to this certificate, contact info@exveritas.com.

ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark.

ExVeritas® is a registered trademark, unauthorised use will lead to prosecution.



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx EXV 19.0031X** Page 1 of 4 [Certificate history:](#)
Status: **Current** Issue No: 0
Date of Issue: 2019-07-12
Applicant: **Pyropress Ltd**
Bell Close
Plympton
Plymouth
Devon
PL7 4JH
United Kingdom
Equipment: **Titan Ex db Switch**
Optional accessory:
Type of Protection: **Flameproof Ex 'db'**
Marking: **Ex db IIB + H₂ T6.....T2 Gb** Tamb -60°C to +40°C.....+90°C

Approved for issue on behalf of the IECEx
Certification Body:

S Clarke CEng MSc MIET

Position:

Certification Manager

Signature:
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

ExVeritas Limited
Units 16-18 Abenbury Way
Wrexham Ind. Est.
Wrexham LL 139UZ
United Kingdom





IECEx Certificate of Conformity

Certificate No.: **IECEx EXV 19.0031X**

Page 2 of 4

Date of issue: 2019-07-12

Issue No: 0

Manufacturer: **Pyropress Ltd**
Bell Close
Plympton
Plymouth
Devon
PL7 4JH
United Kingdom

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[GB/EXV/ExTR19.0035/00](#)

Quality Assessment Report:

[GB/ITS/QAR11.0004/05](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx EXV 19.0031X**

Page 3 of 4

Date of issue: 2019-07-12

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Titan switch is intended to sense changes in temperature, pressure, level or flow via the use of mechanical actuators. The generic two-chamber enclosure is utilised for all applications and is constructed from aluminium LM25TF or material of greater tensile strength. One chamber contains the means (where necessary) of adjusting the set-point(s) whilst the other houses either a single or dual microswitch assembly. The Titan switch possesses five flamepaths. The respective switch outer case-top cover and switch outer case-electrical entry interfaces are of the flange type. The guide-operating rod interface is of the cylindrical type. And the respective switch outer case-guide and electrical entry-adaptor interfaces are of the threaded type with the latter always utilising a suitably certified adaptor. The maximum internal free volume of the flameproof chamber is 99cc. The limits on the ambient and process temperatures and the internal power dissipation shown in the table below ensure that the equipment does not exceed the maximum surface temperature of any given T Class:

T Class	Ambient Temperature Range (°C)	Permitted Process Temperature (°C)	Power Rating (W)
T6	-60 to +75	-60 to +65	2.5
T6	-60 to +70	-60 to +65	5
T6	-60 to +60	-60 to +65	10
T6	-60 to +50	-60 to +65	15
T6	-60 to +40	-60 to +55	20
T5	-60 to +90	-60 to +80	2.5
T5	-60 to +75	-60 to +80	10
T5	-60 to +70	-60 to +75	12.5
T5	-60 to +60	-60 to +70	17.5
T5	-60 to +50	-60 to +65	22.5
T5	-60 to +40	-60 to +60	27.5
T4	-60 to +90	-60 to +130	2.5
T4	-60 to +75	-60 to +130	10
T4	-60 to +70	-60 to +130	12.5
T4	-60 to +60	-60 to +130	17.5
T4	-60 to +50	-60 to +130	22.5
T4	-60 to +40	-60 to +130	27.5
T3	-60 to +90	-60 to +195	2.5
T3	-60 to +75	-60 to +195	10
T3	-60 to +70	-60 to +195	12.5
T3	-60 to +60	-60 to +195	17.5
T3	-60 to +50	-60 to +195	22.5
T3	-60 to +40	-60 to +195	27.5
T2	-60 to +90	-60 to +280	2.5
T2	-60 to +75	-60 to +280	10
T2	-60 to +70	-60 to +280	12.5
T2	-60 to +60	-60 to +280	17.5
T2	-60 to +50	-60 to +280	22.5
T2	-60 to +40	-60 to +280	27.5

SPECIFIC CONDITIONS OF USE: YES as shown below:

Special Conditions for Safe Use

- Flameproof joints not intended for repair



IECEx Certificate of Conformity

Certificate No.: **IECEx EXV 19.0031X**

Page 4 of 4

Date of issue: 2019-07-12

Issue No: 0

- Suitably rated cable must be selected if the equipment is subject to service temperatures of 70°C or greater
- Fasteners associated with the flange flamepaths possess a minimum yield strength of 240 N/mm²

Annex:

[IECExEXV19.0031X Certificate Annex.pdf](#)

Manufacturer's documents:				
Title:	Drawing No.:	Rev	Sheets	Date:
Certification Drawing Titan Ex db Switch	1340/A1	3	1 of 1	16.04.19
Certification Drawing Labels, Titan Ex db Switch	1341/A3	3	1 of 1	16.04.19

Note: An * is included before the title of documents that are new or revised.